



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.
 Media: 100% synthetic fibers, water and bacteria resistant.
 Media bonded to frame using water resistant adhesive.
 Media bonded to expanded metal support grid using water resistant adhesive.

| Air Flow Pleat - 2" Nominal Depth, Standard Capacity | | | |
|--|-----------|------------|-----------|
| Model Number | Width "A" | Height "B" | Depth "C" |
| AFP2000-5502M11 | 24-1/2" | 24-1/2" | 1-3/4" |
| AFP2000-4402M11 | 23-3/8" | 23-3/8" | 1-3/4" |
| AFP2000-0502M11 | 19-1/2" | 24-1/2" | 1-3/4" |
| AFP2000-0402M11 | 19-1/2" | 23-3/8" | 1-3/4" |
| AFP2000-0002M11 | 19-1/2" | 19-1/2" | 1-3/4" |
| AFP2000-8502M11 | 17-3/8" | 24-1/2" | 1-3/4" |
| AFP2000-8402M11 | 17-3/8" | 23-3/8" | 1-3/4" |
| AFP2000-6502M11 | 15-1/2" | 24-1/2" | 1-3/4" |
| AFP2000-6002M11 | 15-1/2" | 19-1/2" | 1-3/4" |
| AFP2000-2402M11 | 11-3/8" | 23-3/8" | 1-3/4" |
| AFP2000-2002M11 | 11-3/8" | 19-1/2" | 1-3/4" |

Notes:

UL 900, Class 2
 30%-35% per ASHRAE 52.1
 MERV 11 per ASHRAE 52.2
 Initial Resistance:
 @ 500 FPM: 0.38" w.g.
 @ 300 FPM: 0.20" w.g.



2294 N. Moraine Dr.
 Dayton, Ohio 45439

Phone: 1-800-699-0747
 Fax: (937) 293-4611

**Air Flow Pleat, 2" Nominal Depth
 Standard Capacity, 55%-60%,
 MERV 11**

| | | | | | |
|----------|----------|-------------|--------------|----------|---|
| Date | 11/04/02 | Part Number | AFP2000-2M11 | Revision | C |
| Approved | | | | | |