



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.

Media: 100% synthetic fibers, water and bacteria resistant.

Media bonded to frame using water resistant adhesive.

Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 4" Nominal Depth, Standard Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP20005504M11	24-1/2"	24-1/2"	3-3/4"
AFP20004404M11	23-3/8"	23-3/8"	3-3/4"
AFP20000504M11	19-1/2"	24-1/2"	3-3/4"
AFP20000404M11	19-1/2"	23-3/8"	3-3/4"
AFP20000004M11	19-1/2"	19-1/2"	3-3/4"
AFP20008504M11	17-3/8"	24-1/2"	3-3/4"
AFP20008404M11	17-3/8"	23-3/8"	3-3/4"
AFP20006504M11	15-1/2"	24-1/2"	3-3/4"
AFP20006004M11	15-1/2"	19-1/2"	3-3/4"
AFP20002404M11	11-3/8"	23-3/8"	3-3/4"
AFP20002004M11	11-3/8"	19-1/2"	3-3/4"

Notes:

UL 900, Class 2

60-65% per ASHRAE 52.1

MERV 11 per ASHRAE 52.2

Media shall be gold in color

Initial Resistance:

@ 500 FPM: 0.35" w.g.



2294 N. Moraine Dr.  
Dayton, Ohio 45439

Phone: 1-800-699-0747  
Fax: (937) 293-4611

**Air Flow Pleat, 4" Nominal Depth  
Standard Capacity, 60 - 65%,  
MERV 11**

Date	2/2/10	Part Number	AFP2000-11	Revision	D
Approved					