



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.

Media: 100% synthetic fibers, non-supportive of bacterial growth

Media bonded to frame using water resistant adhesive.

Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 1" Nominal Depth, High Cap – MERV 11			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-25251M11	24-1/2"	24-1/2"	3/4"
AFP3000-24241M11	23-3/8"	23-3/8"	3/4"
AFP3000-20251M11	19-1/2"	24-1/2"	3/4"
AFP3000-20241M11	19-1/2"	23-3/8"	3/4"
AFP3000-20201M11	19-1/2"	19-1/2"	3/4"
AFP3000-18251M11	17-3/8"	24-1/2"	3/4"
AFP3000-18241M11	17-3/8"	23-3/8"	3/4"
AFP3000-16251M11	15-1/2"	24-1/2"	3/4"
AFP3000-16201M11	15-1/2"	19-1/2"	3/4"
AFP3000-12241M11	11-3/8"	23-3/8"	3/4"
AFP3000-20201M11	11-3/8"	19-1/2"	3/4"

Notes:

UL 900 rated for flammability

MERV 11 per ASHRAE 52.2-2017

Initial Resistance:

@ 300 FPM: 0.22" w.g.

@ 175 FPM: 0.12" w.g.



2294 N. Moraine Dr.
Dayton, Ohio 45439

Phone: 1-800-699-0747
Fax: (937) 293-3975

Air Flow Pleat, 1" Nominal Depth
High Capacity, MERV 11

Date	Part Number	Revision
10/25/23	AFP3000-11	C