



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.

Media: 100% synthetic fibers, water and bacteria resistant.

Media bonded to frame using water resistant adhesive.

Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 4" Nominal Depth, High Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-5504	24-1/2"	24-1/2"	3-3/4"
AFP3000-4404	23-3/8"	23-3/8"	3-3/4"
AFP3000-0504	19-1/2"	24-1/2"	3-3/4"
AFP3000-0404	19-1/2"	23-3/8"	3-3/4"
AFP3000-0004	19-1/2"	19-1/2"	3-3/4"
AFP3000-8504	17-3/8"	24-1/2"	3-3/4"
AFP3000-8404	17-3/8"	23-3/8"	3-3/4"
AFP3000-6504	15-1/2"	24-1/2"	3-3/4"
AFP3000-6004	15-1/2"	19-1/2"	3-3/4"
AFP3000-2404	11-3/8"	23-3/8"	3-3/4"
AFP3000-2004	11-3/8"	19-1/2"	3-3/4"

Notes:

UL 900, Class 2

75 - 80% per ASHRAE 52.1

MERV 13 per ASHRAE 52.2

Media shall be white in color

Initial Resistance:

@ 500 FPM: 0.35" w.g.



2294 N. Moraine Dr.
Dayton, Ohio 45439

Phone: 1-800-699-0747
Fax: (937) 293-4611

**Air Flow Pleat, 4" Nominal Depth
High Capacity, 75 - 80%,
MERV 13**

Date
2/2/10

Part Number

AFP3000-13

Revision

C

Approved