



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.

Media: 100% synthetic fibers, water and bacteria resistant.

Media bonded to frame using water resistant adhesive.

Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 2" Nominal Depth, Standard Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-5502M13	24-1/2"	24-1/2"	1-3/4"
AFP3000-4402M13	23-3/8"	23-3/8"	1-3/4"
AFP3000-0502M13	19-1/2"	24-1/2"	1-3/4"
AFP3000-0402M13	19-1/2"	23-3/8"	1-3/4"
AFP3000-0002M13	19-1/2"	19-1/2"	1-3/4"
AFP3000-8502M13	17-3/8"	24-1/2"	1-3/4"
AFP3000-8402M13	17-3/8"	23-3/8"	1-3/4"
AFP3000-6502M13	15-1/2"	24-1/2"	1-3/4"
AFP3000-6002M13	15-1/2"	19-1/2"	1-3/4"
AFP3000-2402M13	11-3/8"	23-3/8"	1-3/4"
AFP3000-2002M13	11-3/8"	19-1/2"	1-3/4"

Notes:

UL 900, Class 2

60%-65% per ASHRAE 52.1

MERV 13 per ASHRAE 52.2

Initial Resistance:

@ 500 FPM: 0.38" w.g.

@ 300 FPM: 0.20" w.g.



2294 N. Moraine Dr.
Dayton, Ohio 45439

Phone: 1-800-699-0747
Fax: (937) 293-4611

**Air Flow Pleat, 2" Nominal Depth
High Capacity, 60%-65%
MERV 13**

Date	11/04/09	Part Number	AFP3000-2M13	Revision	C
Approved					