



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.
 Media: 100% synthetic fibers, non-supportive of bacterial growth
 Media bonded to frame using water resistant adhesive.
 Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 2" Nominal Depth, Standard Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP2000-25252	24-1/2"	24-1/2"	1-3/4"
AFP2000-24242	23-3/8"	23-3/8"	1-3/4"
AFP2000-20252	19-1/2"	24-1/2"	1-3/4"
AFP2000-20242	19-1/2"	23-3/8"	1-3/4"
AFP2000-20202	19-1/2"	19-1/2"	1-3/4"
AFP2000-18252	17-3/8"	24-1/2"	1-3/4"
AFP2000-18242	17-3/8"	23-3/8"	1-3/4"
AFP2000-16252	15-1/2"	24-1/2"	1-3/4"
AFP2000-16202	15-1/2"	19-1/2"	1-3/4"
AFP2000-12242	11-3/8"	23-3/8"	1-3/4"
AFP2000-20202	11-3/8"	19-1/2"	1-3/4"

Notes:

UL 900 rated for flammability
 40%-45% per ASHRAE 52.1
 MERV 10 per ASHRAE 52.2
 Maximum operating temp 160° F
 Initial Resistance:
 @ 500 FPM: 0.26" w.g.
 @ 300 FPM: 0.14" w.g.



2294 N. Moraine Dr.
 Dayton, Ohio 45439

Phone: 1-800-699-0747
 Fax: (937) 293-3975

**Air Flow Pleat, 2" Nominal Depth
 Standard Capacity, 40%-45%,
 MERV 10**

Date	10/25/17	Part Number	AFP2000-2	Revision	B
Approved					