



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.

Media: 100% synthetic fibers, water and bacteria resistant.

Media bonded to frame using water resistant adhesive.

Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 4" Nominal Depth, Standard Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP20005504	24-1/2"	24-1/2"	3-3/4"
AFP20004404	23-3/8"	23-3/8"	3-3/4"
AFP20000504	19-1/2"	24-1/2"	3-3/4"
AFP20000404	19-3/8"	23-3/8"	3-3/4"
AFP20000004	19-1/2"	19-1/2"	3-3/4"
AFP20008504	17-3/8"	24-1/2"	3-3/4"
AFP20008404	17-3/8"	23-3/8"	3-3/4"
AFP20006504	15-1/2"	24-1/2"	3-3/4"
AFP20006004	15-1/2"	19-1/2"	3-3/4"
AFP20002404	11-3/8"	23-3/8"	3-3/4"
AFP20002004	11-3/8"	19-1/2"	3-3/4"

Notes:

UL 900 rate for flammability

40-45% per ASHRAE 52.1

MERV 10 per ASHRAE 52.2

Initial Resistance:

@ 500 FPM: 0.34" w.g.



2294 N. Moraine Dr.  
Dayton, Ohio 45439

Phone: 1-800-699-0747  
Fax: (937) 293-3975

**Air Flow Pleat, 4" Nominal Depth  
Standard Capacity, 40 - 45%,  
MERV 10**

Date	2/2/18	Part Number	<b>AFP2000-10</b>	Revision	<b>D</b>
Approved					