



**Characteristics**

- Frame: 26 point high wet strength clay-coated kraft board.
- Media: 100% synthetic fibers, water and bacteria resistant.
- Media bonded to frame using water resistant adhesive.
- Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 1" Nominal Depth, High Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-5501	24-1/2"	24-1/2"	3/4"
AFP3000-4401	23-3/8"	23-3/8"	3/4"
AFP3000-0501	19-1/2"	24-1/2"	3/4"
AFP3000-0401	19-1/2"	23-3/8"	3/4"
AFP3000-0001	19-1/2"	19-1/2"	3/4"
AFP3000-8501	17-3/8"	24-1/2"	3/4"
AFP3000-8401	17-3/8"	23-3/8"	3/4"
AFP3000-6501	15-1/2"	24-1/2"	3/4"
AFP3000-6001	15-1/2"	19-1/2"	3/4"
AFP3000-2401	11-3/8"	23-3/8"	3/4"
AFP3000-2001	11-3/8"	19-1/2"	3/4"

**Notes:**

- UL 900, Class 2
- 40%-45% per ASHRAE 52.1
- MERV 10 per ASHRAE 52.2
- Initial Resistance:
  - @ 500 FPM: 0.36" w.g.
  - @ 300 FPM: 0.19" w.g.
  - @ 250 FPM: 0.18" w.g.

2294 N. Moraine Dr. Phone: 1-800-699-0747  
Dayton, Ohio 45439 Fax: (937) 293-3975

**Air Flow Pleat, 1" Nominal Depth  
High Capacity, 40%-45%, MERV  
10**

Date	11/03/17	Part Number	Revision
Approved		<b>AFP3000-10</b>	<b>B</b>