



Characteristics

Frame: 26 pt high wet strength clay-coated kraft board.
 Media: 100% synthetic fibers, water and bacteria resistant.
 Media bonded to frame using water resistant adhesive.
 Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 2" Nominal Depth, High Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-5502	24-1/2"	24-1/2"	1-3/4"
AFP3000-4402	23-3/8"	23-3/8"	1-3/4"
AFP3000-0502	19-1/2"	24-1/2"	1-3/4"
AFP3000-0402	19-1/2"	23-3/8"	1-3/4"
AFP3000-0002	19-1/2"	19-1/2"	1-3/4"
AFP3000-8502	17-3/8"	24-1/2"	1-3/4"
AFP3000-8402	17-3/8"	23-3/8"	1-3/4"
AFP3000-6502	15-1/2"	24-1/2"	1-3/4"
AFP3000-6002	15-1/2"	19-1/2"	1-3/4"
AFP3000-2402	11-3/8"	23-3/8"	1-3/4"
AFP3000-2002	11-3/8"	19-1/2"	1-3/4"

Notes:

UL 900 for Flammability
 40%-45% per ASHRAE 52.1
 MERV 10 per ASHRAE 52.2 - 2017
 Initial Resistance:
 @ 500 FPM: 0.26" w.g.
 @ 300 FPM: 0.14" w.g.



2294 N. Moraine Dr.
 Dayton, Ohio 45439

Phone: 1-800-699-0747
 Fax: (937) 293-3975

**Air Flow Pleat, 2" Nominal Depth
 High Capacity, 40%-45%, MERV
 MERV 10**

Date	11/04/17	Part Number	AFP3000-2	Revision	A
Approved					