



Characteristics

- Frame: 26 point high wet strength clay-coated kraft board.
- Media: 100% synthetic fibers, water and bacteria resistant.
- Media bonded to frame using water resistant adhesive.
- Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 4" Nominal Depth, High Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-5504	24-1/2"	24-1/2"	3-3/4"
AFP3000-4404	23-3/8"	23-3/8"	3-3/4"
AFP3000-0504	19-1/2"	24-1/2"	3-3/4"
AFP3000-0404	19-1/2"	23-3/8"	3-3/4"
AFP3000-0004	19-1/2"	19-1/2"	3-3/4"
AFP3000-8504	17-3/8"	24-1/2"	3-3/4"
AFP3000-8404	17-3/8"	23-3/8"	3-3/4"
AFP3000-6504	15-1/2"	24-1/2"	3-3/4"
AFP3000-6004	15-1/2"	19-1/2"	3-3/4"
AFP3000-2404	11-3/8"	23-3/8"	3-3/4"
AFP3000-2004	11-3/8"	19-1/2"	3-3/4"

Notes:

- UL 900, Class 2
- 40%-45% per ASHRAE 52.1
- MERV 10 per ASHRAE 52.2
- Initial Resistance:
 - @ 500 FPM: 0.28" w.g.
 - @ 300 FPM: 0.22" w.g.



2294 N. Moraine Dr.
Dayton, Ohio 45439

Phone: 1-800-699-0747
Fax: (937) 293-3975

**Air Flow Pleat, 4" Nominal Depth
High Capacity, 40%-45%, MERV
10**

Date
9/9/17

Part Number

AFP3000-4

Revision

B

Approved