


10 Pocket



**Reliable Air Flow
Bag, 85%**

Characteristics

Media: 100% Synthetic Polypropylene Microfiber

Pockets: Ultrasonically Welded Seams & Edges

Pocket Flutes: Ultrasonically Welded Support Spacers

Header: Electro-Galvanized Metal Header and "J" Style Media Retainers

Air Flow Bag 85% - 10 Pocket

Model Number	Width "A"	Height "B"	Depth "C"	Number of Pockets	Air Flow Capacity (cfm)	Initial Resistance ("w.g.)
AFB1085S-4430	23-3/8"	23-3/8"	30"	10	2500	.29
AFB1085S-4426	23-3/8"	23-3/8"	26"	10	1875	.29
AFB1085S-4422	23-3/8"	23-3/8"	22"	10	1875	.29
AFB1085S-4415	23-3/8"	23-3/8"	15"	10	1250	.29
AFB885S-0430	19-3/8"	23-3/8"	30"	8	2000	.29
AFB885S-0426	19-3/8"	23-3/8"	26"	8	1500	.29
AFB885S-0422	19-3/8"	23-3/8"	22"	8	1500	.29
AFB885S-0415	19-3/8"	23-3/8"	15"	8	1000	.29
AFB585S-2430	11-3/8"	23-3/8"	30"	5	1250	.29
AFB585S-2426	11-3/8"	23-3/8"	26"	5	950	.29
AFB585S-2422	11-3/8"	23-3/8"	22"	5	950	.29
AFB585S-2415	11-3/8"	23-3/8"	15"	5	625	.29

Notes:

Standard: UL 900, Class 2

Available with the following
gasketing options:

GU - Gasket Upstream

GD - Gasket Downstream

GS - Gasket Sides

Other Options:

C - Cambridge Header

-1 - UL 900, Class 1

An example of the part number
with options is: AFB1085S-4430GU

DAYTON RELIABLE AIR FILTER

2294 N. Moraine Dr.

Dayton, Ohio 45439

1-800-699-0747



Air Flow Bag 85%, MERV 13,
10 Pocket

Date	Part Number	End Use
Approved	AFB1085S	